


# FULLVIEW & STYLIST

# CHOOSE YOUR OPTIONS

| SPECIFICATIONS                           | Stylist                              | FullView Glass Panel  | FullView Anodized Aluminum Panel |
|--|--------------------------------------|---|----------------------------------|
| <b>U-Factor</b>                          | Not Tested                           | <b>0.85</b>  | Not Tested                       |
| Frame                                    | 6063-T Aluminum                      | 6063-T Aluminum   | 6063-T Aluminum                  |
| Thickness                                | 2 inches                             | 2 inches  | 2 inches                         |
| Glass                                    | ½ inch insulated<br>¾ inch insulated | ½ inch insulated<br>¼ inch non-insulated<br>⅝ inch non-insulated                              | —                                |
| Panel                                    | —                                    | —   | ½ inch insulated                 |
| Rails                                    | Insulated<br>non-insulated           | Insulated<br>non-insulated  | Insulated<br>non-insulated       |
| Air Infiltration Seal                    | •                                    | •   | •                                |
| <b>Warranty*</b> <i>Excludes Springs</i> | 5 years                              | 5 years   | 5 years                          |

\*For full warranty details contact your Midland dealer



## FRAME COLORS



Color Select™

\*ColorSelect™ uses Sherwin Williams Polane® Solar Reflective Polyurethane Enamel, providing a durable, heat-repelling coating.

## GLASS



Plain\*



Obscure



Satin\*\*



Gray Tinted



Bronze



Low E



Double Dark\*

\*Stylist is only available in Plain & Satin Stylist.

\*\*Tempered only. All other glass is available in both tempered and untempered.

## TRACK CONFIGURATIONS



**Standard Lift**  
For normal installations




**Inclined Track**  
To follow pitch of roof



**Hi-Lift**  
To put horizontal track as close to ceiling as possible



**Vertical Lift**  
Full vertical rise where headroom is available



**Low Headroom**  
For low-clearance installations