



Midland's Commercial FullView overhead doors provide strength and durability while allowing in natural light. Make a strong first impression by installing a FullView door, customized with your choice of window glass options. To further complement your building's exterior, choose from our standard frame color options or ask about custom colors.

Available with insulated or non-insulated glass.

THE TECHNOLOGY & STRENGTH OF YOUR FULLVIEW DOOR

Midland's Commercial FullView doors are available in 2-inch and 3-inch thicknesses and multiple window color/design options. Contact your Midland dealer for widths and sizing. All Midland commercial doors feature heavy-duty galvanized steel tracks and hardware.

PICK YOUR GLASS DESIGN

Due to printing processes, colors may not be an accurate representation of the final product. Please contact your midland dealer for authentic colors.



Plain or Plain Tempered



Obscure or
Obscure Tempered



Grey Tinted or
Grey Tinted Tempered



Bronze Tinted or
Bronze Tinted Tempered



Frosted Tempered




Low E or
Low E Tempered

Contact your Midland dealer for more glass window configurations.

CHOOSE YOUR FRAME COLOR

Due to printing processes, colors may not be an accurate representation of the final product. Please contact your Midland dealer for authentic color swatches.



White (2", 3")



Clear Anodized (2")




Deep Bronze Anodized (2")




PICK YOUR OWN
CUSTOM COLOR

FullView doors can be customized to any color of your choice with powder coating options. Contact your Midland dealer for more colors and pricing.


TRACK MOUNTING DETAILS



Bracket Mounted Track
To attach to wood jambs




Reverse Angle Mounted Track
Continuous leg-in angle to attach to steel jambs




Angle Mounted Track
Continuous leg-out angle used on larger doors to attach to wood jambs


TRACK CONFIGURATIONS




Standard Lift
For normal installations



Inclined Track
To follow pitch of roof



High Lift
To put horizontal track as close to ceiling as possible



Vertical Lift
Full vertical rise where headroom is available



Low Headroom
For low-clearance installations

For full commercial track space requirements contact your Midland dealer.

SPECIFICATIONS

Frame	6063-T-6 Aluminum	6063-T-6 Aluminum
Thickness	2 inches	3 inches
Warranty* Excludes Springs	5 years	5 years

*For full warranty details contact your Midland dealer.

Full Box Frame
strengthens the door

Air Infiltration Seal
provides an energy efficient seal to help maintain building temperature



Glass Options

1/2-inch insulated,
1/4-inch non-insulated,
1/8-inch non-insulated



West Fargo, ND 58078
675 12th Ave. NE | 800-437-4056

Eden Prairie, MN 55344
6775 Shady Oak Road | 800-521-0047

Omaha, NE 68138
13661 Giles Road | 800-533-8358

www.midlandgaragedoor.com

Every effort has been made to use accurate photography, drawings, product specifications and descriptions at the time of printing. However, because of continuous progressive product improvements, all specifications and descriptions are subject to change without prior notice. Certain features shown are non-stock items and may be purchased through Midland Garage Door Manufacturing Company's sales offices or through an authorized dealer.

© 2017 Midland Garage Door Mfg. Co. Inc. All rights reserved. 0417